

STANDARD HORIZON

Nothing takes to water like Standard Horizon

Intrinsically Safe
VHF FM Marine Transceiver

HX400IS

COMMERCIAL VHF WITH LMR CHANNELS



- 40 Programmable Land Mobile Channels 134MHz to 174MHz with CTCSS and DCS signaling
- Intrinsically Safe (ANSI/UL913 rated)
- Supplied with 2300mAh Li-Ion battery, AC 3-hour quick charger
- Selectable 5/1 W transmit power output
- Submersible IPX8 (1.5m for 30minutes)
- Programmable channel names
- Built-in Noise Canceling Microphone and Voice Scrambler for clear and private communications
- Battery life indicator
- All USA, International And Canadian Marine Channels
- NOAA Weather Channels and Weather Alert
- Preset key used to recall up to 10 favorite channels
- Programmable Scan, Priority Scan, Dual Watch and TRI-Watch
- Optional speaker microphones and headsets available



Actual Size

STANDARD HORIZON

Nothing takes to water like Standard Horizon

Intrinsically Safe VHF FM Marine Transceiver

HX400IS

Marine and Land Mobile Channels

The HX400IS is factory programmed with all International, USA, Canadian and NOAA Weather channels. It also has the capability to be programmed with 40 Land Mobile Radio (134-174MHz) channels with CTCSS or DCS signaling by a Standard Horizon dealer.

Lithium-ion battery and rapid charger

The HX400IS is supplied with a large capacity 2300mAh Lithium-Ion battery, with an expected operating time of up to 17 hours. The radio is supplied with a 3 hour rapid charger for minimum down time.

Built-in Noise Canceling Mic and Voice scrambler

Expect clear communications, the built-in Noise Canceling microphone is engineered to cancel out external noise when operating in a busy environment. Expect private communications, with an internal 4 code scrambler compatible with other Standard Horizon Hand held radios and Fixed mount radios with a 4 code scrambler installed.

Loud audio

The HX400IS is designed to be heard in even the noisiest environments with 700mW of power supplied to the internal speaker.

Programmable Scan, Priority Scan and Dual Watch

Scanning is made simple with the HX400IS. The radio can be setup to scan any number of channels with or without a priority channel or simply can be setup to scan between a priority channel and one or two other channels (Dual and TRI-Watch)

INTRINSICALLY SAFE (IS) INFORMATION

The **HX400IS**, equipped with any of the following optional units, meets the requirement of ANSI/UL 913-5th Edition for Class I, II, III Division 1, Group C, D, E, F, G, T3 for hazardous locations.

Battery Pack: **FNB-115LIIS (Li-Ion battery pack)**

Speaker Microphones: **SSM-14A and CMP460**

SPECIFICATIONS

| General | |
|------------------------------|---|
| Frequency Range (MHz) | Marine Band / WX Band: 156.025 MHz - 163.275 MHz LMR Band: 134.000 MHz - 174.000 MHz |
| Number of LMR Channels | 40 |
| Channel Steps | 25 kHz (25.0/12.5 kHz LMR) |
| Frequency Stability | ±2.5 ppm (-30° C to 60° C) |
| Emission Type | 16K0G3E, 16K0F3E, 11K0F3E |
| Antenna Impedance | 50 Ohms |
| Supply Voltage | 7.4 V DC |
| Current Consumption | 320 mA (Receive), 50 mA (Standby) TX: 1.6 A (H)/0.8 A (L) |
| Operating Temperature | -30° C to +60° C |
| Waterproof rating: | IPX8 (1.5 m for 30 minutes) |
| Case Size (W x H x D) | 57 x 133 x 40 mm w/o knob & antenna |
| Weight (Approx.) | 350 g with FNB-115LIIS |
| Transmitter | |
| RF Output Power | 5 W / 1 W (@7.4 V) |
| Maximum Deviation | ±5 kHz (Wide) / ±2.5 kHz (Narrow) |
| Spurious Emission | At least -36 dBm below |
| Microphone Impedance | 2 k-Ohm |
| Receiver | |
| Circuit Type | Double-Conversion Superheterodyne |
| Sensitivity | 0.25 µV/12 dB SINAD |
| Adjacent Channel Selectivity | 70 dB (Wide) / 60 dB (Narrow) |
| Intermodulation response | 68 dB (typical) |
| Selectivity | 12 kHz / 25 kHz (-6 dB / -60 dB) (Wide) 6 kHz / 18 kHz (-6 dB / -60 dB) (Narrow) |
| AF Output (Internal SP) | 700 mW @16 Ohm for 10 % THD (@7.4 V) |

Standard Horizon reserves the right to make changes and enhancements to products at our discretion. Current specifications are therefore subject to change without notice.

INCLUDED ACCESSORIES

FNB-115LIIS
Li-Ion Battery Pack



PA-45
Charger



CD-50
Charger Cradle



CAT460
Antenna



CLIP-22
Belt Clip



HAND STRAP

OPTIONAL ACCESSORIES

SSM-14A*
Submersible
speaker
microphone



CMP460*
Submersible
speaker
microphone



E-DC-30
DC cable with
Cigarette lighter
plug used
with CD-50



SAD-1460
6 unit Multi Charger



* Intrinsically Safe Version

STANDARD HORIZON

YAESU USA

6125 Phyllis Drive, Cypress, CA 90630

Phone: (800)767-2450

Fax: (800)552-6813

WWW.STANDARDHORIZON.COM

2015. 1005NP(USA) B9200748 Printed in Japan



"Standard Horizon makes every effort to keep our oceans blue. This catalog was produced with the environment in mind please recycle."

Distribuidor oficial Yaesu

RYDER

Informatica y comunicaciones

Mendoza 4834 4° A - 1431 CABA

Tel: 5368-9940